



Type Designation	6106
System	Lithium / Iron Disulfide (Li/FeS ₂)
Shelf Life (Coding)*	15 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	2900
Permissible Temperature Range	- 40 °C ... 60 °C
Weight, approx. [g]	15
Short circuit current [A]	8

Dimensions [mm] min: max:

Ø	13.5	14.5
A	-	50.5
B	49.5	-
E	-	0.5
F	-	5.5
G	1.0	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	1.05
2S/28S, 5M/H	1500 mW/650mW	Pulse [n]	480
Digital Still Camera			
Discharge Type	Load	End Voltage[V]	0.9
10S/M, 1H/D, 7D/W	1000 mA	Pulse [n]	880
Photo Flash			
Discharge Type	Load	End Voltage[V]	0.9
1H/D, 7D/W	250 mA	Time [h]	10,0
CD / MD / Electronic game			

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.

VARTA Consumer Batteries GmbH & Co. KGaA
Alfred-Krupp-Str. 9, 73479 Ellwangen/Germany

Subject to change without prior notice
Page 1 / 1 Date of issue: 2015-10-15

Phone: (+49) 7961/83-0, Fax: (+49) 800-827-8274